

In cooperation with the Bureau of Land Management

## Erosion Resistance and Dust Emission on the Milford Flat Fire --Can ESR Treatments Sometimes Worsen Wind Erosion?

#### Introduction

A major objective of post-fire Emergency Stabilization & Rehabilitation (ESR) treatments is to enhance erosion resistance and stabilize burned areas through the establishment of vegetation. Yet because mechanical treatments such as chaining and seeding with rangel and drills disturb soils for purposes of seed burial, ESR treatments also can have adverse impacts on soil stability. Treatment impacts on soil stability and erosion resistance generally are assumed to represent short-term trade-offs that are necessary for achieving long-term stabilization. Yet post-treatment monitoring efforts are rarely designed specifically to measure erosion resistance or soil movement, and there is no published research that examines treatment effectiveness in reducing rates of winderosion and dust emission. To address this need for information, the U.S. Geological Survey (USGS) and the Bureau of Land Management (BLM) are collaborating on a project to monitor effects of ESR treatments on erosion resistance and dust emission in a portion of the Milford Flat Fire in west-central Utah. This project examines the effectiveness of ESR treatments in relation to treatment type, soil properties, and landscape setting.

#### Study Area - Milford Flat Fire The Milford Flat Fire burned 147,000 ha (363,000 ac) in the eastern Great Basin in July 2007 and was the largest wildfire in Utah history. Within the fire perimeter, elevation ranges from 1390 to 2775 m and mean annual precipitation (MAP) ranges from 230 mm to 590 mm. Dust monitoring plots are located in the northwestern section of the bum where field observations and satellite imagery

Aridity (P/PET) (UNESCO classes)

Semiarid

Subhumid

Milford Flat Fire on 4/15/08.

Soil Texture

& Crusting

Figure 1. Conceptual diagram illustrating relative effects of fire and

mechanical ESR treatments on attributes related to erosion resistance.

Figure 2. Location (a) of the Milford Flat Fire in westcentral Utah, and (b) satellite image showing a dust plume emitted from within the fire perimeter while ESR treatments were being conducted in April 2008.

grained lacustrine sediments, unburned vegetation is dominated by shadscale (Atriplex confertifolia) and gray molly (Bassia americana) with well-developed biological crusts (Fig. 3a). Dune sands are dominated by four-wing saltbush (Atriplex canescens), Mormon tea (Ephedra sp.), and perennial grasses including Indian ricegrass (Stipa hymenoides), needle-and-thread (S. comata), and western wheatgrass (Elymus smithii).

Iford Flat Fire

#### Study Design

Twenty-four monitoring plots were established in August 2008 to examine attributes of erosion resistance and seasonal patterns of dust emission in relation to three factors --

Unburned salt desert scrub

#### 1. Substrate

- Fine-grained lacustrine sediments -Dune sands

detected high levels of dust emissions during spring

2008 (Fig. 2). In this region of the burn, elevation is

1415-1500 m and MAP is 250-290 mm. Soils are

derived from Pleistocene-aged lacustrine sediments

with silty clay loam (lacustrine sediments) and fine

and dune sands associated with Lake Bonneville,

sandy (dune sands) surface textures. On fine-

- 2. Burn status
- Unburned

#### 3. Type of ESR treatment

- Aerial seeding + Bly chain
- Rangeland drill
- Plateau herbicide + rangeland drill

# and biological crust (inset)




Figure 3. Unburned salt desert scrub (a) dominated by shadscale and biological soil crust on fine-grained lacustrine sediments, and (b) burned areas treated with a rangel and drill

#### **Field Methods**

Soil and vegetation attributes related to erosion resistance are measured annually (Jul-Aug 2008-2010) using sampling techniques recommended for monitoring post-fire ESR treatments (Herrick et al. 2005, Wirth and Pyke 2006). Sampling occurs along three 50-m transects oriented as spokes radiating from the center of the plot. Attributes and sampling techniques include --

- Ground cover and foliar cover by species (line-point intercept technique),
- Gaps between plant canopies (line-intercept technique),
- Soil aggregate stability (field slake test), and
- Soil surface roughness (chain method; Saleh 1993).

Dust emissions are monitored with BSNE dust samplers mounted on a metal pole at the center of each plot at 15, 50, and 100 cm heights above the soil surface (Fig. 4; Fryear 1986). Dust samples are collected three times per year (1) Jul, 1 Nov, and 1 Mar) to coincide with collection dates for other dustmonitoring efforts in the region.




Figure 4. BSNE dust sampler used for monitoring dust emissions.

#### Results

#### Erosion Resistance

Data collected in August 2008 (one year post-fire) indicate that plots in treated areas were least resistant to wind erosion relative to plots in unburned areas and in burned areas that did not receive ESR treatments. Average bare ground was 46.4% in unburned plots, 68.7% in burned plots that were not treated, and 85.5% in burned plots that received ESR treatments (Fig. 5a). On fine-grained lacustrine sediments, burned plots receiving ESR treatments had soil aggregate stability values that were significantly lower than values in unburned plots and in burned plots that were not treated (Fig. 5b). Gaps between plant canopies also were largest in plots that received ESR treatments relative to unburned plots and burned plots that did not receive

ESR treatments (Fig. 6)

Horizontal Dust Flux

During the Aug-Oct 2008

burned/untreated plots, and

17.6 - 19,800.4 g m<sup>-2</sup> day<sup>-1</sup>

received ESR treatments

(Fig. 8). Maximum dust

fluxes in plots that received

ESR treatments were 2.0 -

maximum fluxes (approx

documented during nine

elevation sites on the

et al., submitted).

years of monitoring at low-

Colorado Plateau (Belnap

5.8 times greater than

 $3,400 \text{ g m}^{-2} \text{ day}^{-1}$ 

in burned plots that





Figure 5. (a) Percent bare ground (means  $\pm 95\%$  CI) and (b) soil aggregate stability (means ± 1 SE) in August 2008 in unburned plots, burned / untreated plots, and plots receiving ESR treatments. Means annotated with the same letter are not significantly different.

## 15-cm Dust Flux, Aug-Oct 08






Figure 8. Horizontal dust fluxes at 15 cm during the period Aug-Oct 2008 in relation to landscape setting (protected or exposed), substrate, and treatment type (unburned; burned but untreated; and chained, drilled, or sprayed and drilled). (Data from upper panel are included in lower panel -- note difference in scaling of y-axes.)

# Canopy Gaps, Aug 08 Burned (median = 96.0 cm)

Figure 6. Percent of total transect length in size classes of canopy gaps in unburned plots, burned / untreated plots, and plots that received ESR treatments.

(median = 663.0 cm)



Figure 7. A canopy gap (from Herrick

Figure 9. Map of plot locations in study area at northern end of the Milford Flat Fire, with plot symbols (red points) scaled by Aug-Oct 08 dust fluxes at 15 cm. Note that symbols are graduated, not proportional. See Fig. 8 for actual flux values.

#### Discussion

Wind Erosion -- Controlling Factors Beyond Management Control Several factors beyond management control contribute to the high potential for wind erosion in the study area.

- Highly Susceptible Soils: Dune sands provide an abundant source of saltating soil particles that sand-blast fine-grained lake sediments, causing them to become suspended and transported far downwind (Okin et al. 2006).
- Arid Climate: The study area is <u>arid</u> (Fig. 2a), thus resulting in a low probability of plant establishment in response to ESR treatments.
- Highly Exposed Landscape Setting: The area is situated on a basin floor with a *very high degree of wind exposure* and wind corridors created by topographic features. (Aerial photographs illustrate the dominance of eolian landforms, and a wind farm is under construction south of the study area.)




Figure 10. (a) Swath of well-developed biological soil crust between furrows created by a rangeland drill, and (b) a dust plume arising from a burned area treated with herbicide and a rangeland drill.

#### Effects of Fire and ESR Treatments on Erosion Resistance and Dust Emission

In settings such as the study area where there is a naturally high potential for winderosion, it is especially important for decision makers to critically evaluate relative impacts of fire and ESR treatments on erosion resistance. Data collected one year post-fire strongly suggest that ESR treatments thus far have had greater adverse impacts on erosion resistance than the fire itself. This is primarily due to treatment impacts on soil erodibility (destabilization of soils through disturbance of intact biological crusts, and alignment of drill furrows with prevailing winds), and secondarily due to treatment impacts on vegetation structure (suppression of annual plants). Where such impacts of ESR treatments coincided with highly exposed landscape settings and highly susceptible soils (fine-grained lacustrine sediments with a veneer of fine sand), it is probable that treatments themselves greatly contributed to the high dust emissions detected by satellite imagery (Fig. 2b) and documented during the first period of dust sampling (Fig. 8). These dust emissions have the potential to impact air quality, the duration of mountain snowcover (Painter et al. 2007), and alpine ecosystems (Neff et al. 2008) far downwind of the study area.

#### How do we Assess Risks of Post-Fire Treatment Strategies?

Recent advances in erosion modeling have the potential to improve managers" ability to evaluate the relative importance of vegetation structure and soil-surface properties as dynamic controls of wind erosion in different landscape settings (Okin et al. 2006, Okin 2008). Such information can be used to enhance decision makers' ability to assess relative risks of different management strategies, whether in relation to fire or other issues.

Motivated in part by this research, Figure 11 presents a conceptual model illustrating the interactive effects of vegetation structure (scaled canopy gaps) and soil erodibility on wind erosion. Curves illustrate the sensitivity of wind erosion to changes in soil erodibility for a fixed configuration of vegetation structure (e.g., x, in Fig. 11a). Notably, the model suggests that as gap sizes increase (i.e., as plants become smaller and spaced farther apart), there is a level  $(x_2)$  beyond which wind erosion becomes relatively insensitive to vegetation structure and is almost entirely controlled by soilsurface properties that determine erodibility. This has tremendous implications for management of and landscapes with naturally low amounts of vegetative cover (e.g., Fig. 3a).

These concepts can be applied to illustrate relative effects of fire and ESR treatments on wind erosion in the study area (Fig. 11b). Wildfire reduced vegetation structure but had lesser direct impact on soil erodibility (e.g., Fig. 5b), resulting in a slight increase in wind erosion (shift from 1 to 2 in the diagram). ESR treatments further reduced vegetation structure (in short term), but had relatively large impacts on soil erodibility -- resulting in a large increase in wind erosion (shift from 2 to 3 in the diagram).

## of vegetation structure and soil erodibility on wind erosion Biological crust: Physical crusts b. Relative effects of fire and ESR treatments on wind erosion, based on data collected for this project

a. Hypothetical family of curves (solid) illustrating interactive effects




Figure 11. (a) Conceptual model illustrating interactive effects of vegetation structure and soil erodibility on wind erosion, and (b) application of the model to illustrate relative effects of fire and ESR treatments on wind erosion in the study area (motivated by Okin 2008 and Okin et al. 2006). See text for explanation.

### Take-Home Points

- Monitoring is rarely conducted to evaluate effects of post-fire ESR. treatments on erosion resistance and dust emission.
- Data collected thus far suggest that ESR treatments in the study area had greater adverse impacts on erosion resistance and dust emission
- than the fire itself.
- Managers need better tools for assessing relative risks of different post-fire management strategies, particularly in arid landscapes where climatic conditions greatly limit plant establishment and the effectiveness of post-fire ESR treatments.

#### Acknowledgements

Funding support has been provided by the Bureau of Land Management and the U.S. Geological Survey (Global Change Program and Southwest Biological Science Center).

Literature Cited Fryrear, D. W. 1986. Afield dust sampler. Journal of Soil and Water Conservation 41:117-120.

Herrick, J.B., J.W. Van Zee, K. M. Havstad, L. M. Burkett, and W. G. Whitford. 2005. Monitoring manual for grassland, shrubland and savanna ecosystems. Volume 1: Quick start. USD A-ARS Jornada Experimental Range, Las Cruces, NM [available on the World Wide Web at URL http://usda-ars.nmsu.edu/jer/monit\_assess/monitoring.htm].

Painter JT. H. JA. P. Barrett JC. C. Landry J. C. Neff JM. P. Cassidy JC. R. Lawrence JK. B. McBride Jand G. L. Farmer. 2007. Impact of disturbed desert soils on duration of mountain snow cover. Geophysical Research Letters 34: L12502.

Neff J. C., A. P. Ballantyne, G. L. Farmer, N. M. Mahowald, J. L. Conroy, C. C. Landry, J. T. Overpeck, T. H. Painter, C. R. Lawrence, and R. L. Reynolds, 2008. Increasing eolian dust deposition in the western United States linked to human activity. Nature Geoscience 1: 189-195.

Okin, G. S. 2008. Anew model of wind erosion in the presence of vegetation. Journal of Geophysical Research 113: F02S10, doi:10.1029/2007JF000758.

Okin, G. S., D. A. Gillette, and J. B. Herrick. 2006. Multi-scale controls on and consequences of aeolian processes in landscape. change in arid and semi-arid environments. Journal of Arid Environments 65: 253-275.

Saleh, A. 1993. Soil roughness measurement: chain method. Journal of Soil and Water Conservation 48: 527-530.

Wirth, T. A., and D. A. Pyke. 2006. Monitoring post-fire vegetation rehabilitation projects: A common approach for non-forested ecosystems. U.S. Geological Survey Scientific Investigations Report 2006-5048 [available on the World Wide Web at URL http://pubs.usgs.gov/sir/2006/5048/.].

Contact Mark E. Miller U.S. Geological Survey Southwest Biological Science Center c/o Grand Stairc ase-Escalante National Monment Kanab, UT 84741 Email: Mark\_Miller@usgs.gov

Tele: 435.644.4325

U.S. Department of the Interior U.S. Geological Survey